

MONARFLEX FIXING ACCESSORIES

Anchor & Strap This two-piece flexible fixing accessory, consists of a specially designed user friendly piercing Anchor, which together with the strong oval shaped Rubber Strap ensure an exceptionally strong and flexible fixation to the scaffold structure. It is the ideal fixing accessory to use when high wind resistance is required.

Strength at break: > 75 kg



Fixostrap This is a one-piece rigid tight fitting accessory that is very quick to mount. It is highly suitable when the Monarflex eyelet is directly in front of the scaffold tube. The piercing Anchor attaches the sheeting to the scaffold tube by means of a cable tie that can be tightened and loosened to get just the right fit.

Strength at break: > 45 kg



System Tie This is a one-piece flexible fixing accessory, consisting of a piercing anchor and a flexible rubber strap with a carbine hook at the end. The very pointed piercing anchor penetrates the sheeting with ease, which makes it fast and easy to mount. The system tie does not need to be fixed directly in front of the framework, as it can be fixed with the carbin hook on the rubber strap or directly onto the scaffold frame.

Strength at break: > 40 kg



Flexitie The standard versatile and flexible fixing for use on most scaffold installations.

Strength at break: > 45 kg



Monostud The Monostud is to be used in combination with a cable tie. The purpose is to give a complete water tight solution. The monostud with a cable tie (strap) mounted in the fixing hole is pressed into the eyelet of the sheeting from the outside. Finally, the strap is tied directly on to the framework, hence closing the eyelet and making it watertight.

Load to failure: > 35 kg



Polytoggle The Polytoggle is a unique piece which ensures a water tight fixing. The Polytoggle is pressed into the eyelet of the sheeting from the outside, after the eyelet hole has been trimmed of excess sheeting with a cutter. A strap, a rope, a wire or similar is inserted in the Polytoggle and tied to the scaffold framework.

Load to failure: > 35 kg



Wedge and Strap As an accessory to the Polytoggle a wedge and strap can be used giving a flexible (elastic) water proof fixing. The Polytoggle is pressed into the eyelet of the sheeting to give a water tight fixing. The wedge is then slid into the opening of the Polytoggle and fixed to the framework with the rubber band.

Strength at break: > 20 kg



T-Clamp This unique two-part fixing accessory is used to join two sheets together through the overlapping eyelets. The T-clamp cannot be fixed to the scaffold tube and has a limited resistance against wind loads.

Strength at break: > 35 kg



Monarflex Clear Tape This is a very durable clear PVC tape with a width of 50 mm and a thickness of 0.15 mm. It is flame retardant and stabilised against UV degradation. Monarflex Clear Tape is used to repair damages in the sheeting and can additionally be used to secure overlaps, in order to completely seal the sheeting.

Elongation: 130%. Service Temp: 0°C to 70°C. Application Temp: 5°C to 40°C



Monarpunch This is a small plastic hand tool used to pre-pierce or puncture the hole through the eyelet of the sheeting. When having to pierce several hundreds of eyelets in a day, this small tool can be quite useful

