

MONARFLEX Light

Technical Data Sheet

Features

MONARFLEX Light is a product from the broad MONARFLEX range of scaffold sheeting. The composition of the product is a strong 12x12mm reinforcement grid in 1100 dtex Polyester yarn protected by 2 layers of Low Density Polyethylene (LDPE) with UV stabilisation.

Durability

We recommend that MONARFLEX Light be used for medium term projects up to 6 months duration. The sheeting can be used for temporary covering of scaffolds or other objects that need to be protected from either the weather or other mechanical influences.

Application

MONARFLEX Light can be applied both vertically and horizontally. The fixing method suits most standard scaffolding systems. Fixing the sheeting to the scaffold must be done according to calculations taking factors like wind and height of the surrounding buildings into consideration. We recommend the use of 1 fixing/m² but any fixing must be placed according to calculations for each project.

| | |
|---------------------------------|-------------------------------------|
| Available Sizes | 2m x 45m |
| Roll Weight | 16.2 kg |
| Gross Weight | 180 g/m ² |
| Tensile Strength | >7.5 kN/m |
| Eyelet Pull-out Strength | 386 N |
| Tear Strength | 210 N |
| Light Transmission | 80% |
| Material | Reinforced Low Density Polyethylene |
| Colour | Clear |